



Product specification sheet

Product title | 3R2222-12B-CW SKB 3R case 559x559x305 (229+76) mm; Cubed Foam, pull handle & wheels



Description

These Mil-Standard cases were designed to meet the most demanding military specifications. They are roto-molded for strength and durability, airtight and water proof with solid stainless steel latches and hinges that will withstand the most demanding shipping conditions.

The 3R Mil-Std. Cases are molded of (LLDPE) polyethylene impact resistant / UV stabilized material and meet or exceed MIL-STD 810 and MIL-C-4150J specifications.

The shipping cases are all available with an empty interior while some models are available with: cubed foam, layered foam, padded dividers, and a pull handle with wheels. Most models without a built-in pull handle or tow handle accommodate a field installable caster kit which is sold separately.

Features

- Waterproof and dust tight design (MIL-C-4150J)
- LLDPE Polyethylene impact resistant
- UV, solvents, corrosion, fungus resistant (MIL-STD-810F)
- Pressure relief / breather valves
- Resistant to impact damage (MIL-STD-810F)
- Stainless steel latches and hinges

Specifications

• Interior Length	55.9 cm	22.1 inch
• Interior Width	55.9 cm	22.1 inch
• Interior Height	30.5 cm	12.1 inch
• Base Depth	22.9 cm	9.1 inch
• Lid Depth	7.6 cm	3.0 inch
• Exterior Length	66.0 cm	26.0 inch
• Exterior Width	66.0 cm	26.0 inch
• Exterior Height	34.3 cm	13.6 inch
• Carton Length	67.0 cm	26.4 inch
• Carton Width	66.6 cm	26.3 inch
• Carton Depth	37.0 cm	14.6 inch
• Shipping Weight	14.8 kg	32.6 lb
• Product Weight	13.4 kg	29.5 lb
• Cubed Foam		
• ATA Rated		