



Product specification sheet

Product title | 3R2222-20B-E SKB 3R case 559x559x508 (419+89) mm; Empty



Description

These Mil-Standard cases were designed to meet the most demanding military specifications. They are roto-molded for strength and durability, airtight and water proof with solid stainless steel latches and hinges that will withstand the most demanding shipping conditions.

The 3R Mil-Std. Cases are molded of (LLDPE) polyethylene impact resistant / UV stabilized material and meet or exceed MIL-STD 810 and MIL-C-4150J specifications.

The shipping cases are all available with an empty interior while some models are available with: cubed foam, layered foam, padded dividers, and a pull handle with wheels. Most models without a built-in pull handle or tow handle accommodate a field installable caster kit which is sold separately.

Features

- Waterproof and dust tight design (MIL-C-4150J)
- LLDPE Polyethylene impact resistant
- UV, solvents, corrosion, fungus resistant (MIL-STD-810F)
- Pressure relief / breather valves
- Resistant to impact damage (MIL-STD-810F)
- Stainless steel latches and hinges

Specifications

• Interior Length	56.2 cm	22.2 inch
• Interior Width	56.2 cm	22.2 inch
• Interior Height	50.5 cm	19.9 inch
• Base Depth	41.3 cm	16.3 inch
• Lid Depth	9.2 cm	3.7 inch
• Exterior Length	66.0 cm	26.0 inch
• Exterior Width	65.4 cm	25.8 inch
• Exterior Height	57.2 cm	22.6 inch
• Carton Length	68.0 cm	26.8 inch
• Carton Width	66.0 cm	26.0 inch
• Carton Depth	58.0 cm	22.9 inch
• Shipping Weight	15.0 kg	33.1 lb
• Product Weight	12.8 kg	28.2 lb
• ATA Rated		
